

endorstanding of the povingement world

SEISMIC DATA LABORATORY QUARTERLY TECHNICAL SUMMARY REPORT JANUARY - MARCH 1972

15 APRIL 1972

AIR FORCE TECHNICAL APPLICATIONS CENTER Washington, D.C.



Project VELA UNIFORM

Epocord by ADVANCED RESEARCH PROJECTS AGENCY Nacion Monitoring Research Office ARPA Order No. 1714

TELEDYNE GEOTECH


NATIONAL TECHNICAL INFORMATION SERVICE ALEXAMBRIA LABORATORIES

APPRATED FOR PUBLIC RELEASE; WISTBIBUTION CHLIMITED.

See AD 736 253

10

Maither the Advanced Research Projects Agency nor the Air Fercy Technical Applications Center will be responsible for information contents of herein which has been supplied by other organizations or sustractors, and this document is subject to later revision as may be necessary. The views and conclusions presented are those of the outhers and about not be incorporated an necessarily representing the afficial policies, either expressed or insplied, of the Advanced Research Projects Agency, the Air Force Technical Applications Contents of the U.S. Government.



Unclassified
Security Classification DOCUMENT CONTROL DATA - RED (Security classification of title, body of abetract and indexing annalation must be only I: ORIGINATING ACTIVITY (Comparete author Teledyne Geotech Alexandria, Virginia S REPORT TITLE SEISMIC DATA LABORATORY QUARTERLY TECHNICAL SUMMARY REPORT a. DESCRIPTIVE NOTES (Type of report and inclusive detec) Scientific 8. AUTHOR(8) (Lool name, Brot Rease, IniHal) Hartenberger, R.A. 4. REPORT DATE 15 April 1972 SO CONTRACT OR GRANT NO.

74. TOTAL NO. OF PAGES 75. NO. OF REFS

. REPORT SECURITY C LASSIFICATION

Unclassified

--

So. ORIGINATOR'S REPORT NUMBER(\$)

96. OTHER REPORT HO(8) (Any other numbers that may be seeigned

IS AVAILABILITY/LIMITATION NOTICES

ARPA Program Code No. 2F10

ÄRPA Order No. 1714

approves the module colored, neathering decimasay,

11 SUPPLEMENTARY NOTES

F33657-72-C-0009

A PROJECT NO. VELA T/2706

> 12. SPONSORING MILITARY ACTIVITY Advanced Research Projects Agency Nuclear Monitoring Research Office Washington, D.C.

13 ABSTRACT

This report summarizes the work done by the SDL during the period January through March 1972, and primarily concerns the seismic research activities related to the detection and identification of nuclear explosions and earthquakes. The report also contains brief discussions of the support tasks and data services which were performed for other government contractors and for participants in the VELA-UNIFORM and PRIME ARGUS projects.

14 KEY WORDS

Seismic Data Laboratory - Quarterly Technical Summary VELA-UNIFORM Project

Unclassified

Security Classification

SEISMIC DATA LABORATORY QUARTERLY TECHNICAL SUMMARY REPORT

January - March 1972

AFTAC Project No.: VELA T/2706

Project Title: Seismic Data Laboratory

ARPA Order No.: 1714

ARPA Program Code No.: 2F10

Name of Contractor: TELEDYNE GEOTECH

Contract No.: F33657-72-C-0009

Date of Contract: 01 July 1971

Amount of Contract: \$1,314,000

30 June 1972 Contract Expiration Date:

Royal A. Hartenberger (703) 836-3882 Project Manager:

P. O. Box 33%, Alexandria, Virginia

APPROYED FOR PUBLICABLE LE. MICTRIBUTION UNLIMITED.

TABLE OF CONTENTS

SECTION		PAGE NO.
	ABSTRACT	-
I.	INTRODUCTION	1
II.	WORK COMPLETED	. 1,
	A. Single Station and Array Methods for Improved Surface Wave Spectral Estimates, No. 264	1
	B. Generalized Linear Filtering of Seismic Array Data, No. 269	. 1
	C. Analysis of Short-Period Seismic Signals and Noise Recorded at LASA and TFO, No. 276	2
	D. Effects of Propagation Paths On Surface-Wave Magnitude Estimates, No. 279	2
	E. A Comparative Study of the Elastic Wave Radiation From Earthquakes and Underground Explosions, No. 284	2
	F. Automatic Network Detection, No. 285	3
	G. Source Time Functions and Spectra for Underground Nuclear Explosions, No. 288	3
III.	SUPPORT AND SERVICE TASKS	
	A. Data Cataloging, Classifying and Retrieval	4
	B. Equipment Modifications	4
	C. Maintain and Operate Equipment	4
	D. Digital Programming	5
	E. VELA and PRIME ARGUS Data Copies	5
	F. Analog Field Tape Supply	5
	C. Array Data Sarvica	ε

ABSTRACT

This report summarizes the work done by the SDL during the period January through March 1972, and primarily concerns the seismic research activities related to the detection and identification of nuclear explosions and earthquakes. The report also contains brief discussions of the support tasks and data services which were performed for other government contractors and for participants in the VELA-UNIFORM and PRIME ARGUS projects.

I. INTRODUCTION

This quarterly report summarizes the technical work, support effort, and data services completed during the period January through March 1972. Current and past work are mentioned only if related to the present discussions.

Reviews of technical reports completed during the reporting period are contained in Section II under descriptive headings. Section III is a summary of the support and service tasks performed for other government contractors and for VELA-UNIFORM and TRIME ARGUS participants.

II. WORK COMPLETED

A. Single Station and Array Methods for Improved Surface Wave Spectral Estimates

This report discusses combined matched filtering and array summing methods which have been developed to yield improved spectral estimates for weak surface waves. Both theoretically and experimentally the best spectral estimates are obtained by first beaming an array of individual matched filtered seismograms and then computing a single noise-corrected spectrum. Spectral results for test cases and actual events are compared using three different techniques. Computer programs implementing these spectral methods have been written which are suitable for routinely processing many events.

B. Generalized Linear Filtering Seismic Array Data

In this investigation the theory of generalized linear filtering is applied to the problem of averaging the transfer functions between a seismin source and seismic recording stations on a continental-sized array.

To provide synthetic data for a test of the processor, a simple source signal is passed through nine different random perturbations of a velocity-depth structure yielding nine different synthetic seismograms. Two nuclear explosions (LONG SHOT and MILROW) and an Andreanoff Island event (22 November 1965) are also processed using stations from the Long-Range-Seismic-Measurement net. Most of the reverberations are removed from the synthetic seismogram by generalized linear filtering. The explosion and the earthquake seismograms are simplified by this process.

The earthquake appears to have longer time terms remaining after generalized linear filtering and the nuclear events appear more similar (before the arrival of the depth phase).

C. Analysis of Short-Period Seismic Signals and Noise Recorded at LASA and TFO

Short-period beams were formed for twenty-four events recorded at both the LASA and TFO arrays. The mean rms noise in the frequency range 0.4-3.0 Hz for the LASA beams was 0.16 mu, and for the TFO beams 0.13 mu. Noise reduction by beam forming in the frequency range 0.4-3.0 Hz varied from 17 to 23 db for LASA, from 12 to 18 db for the 37-sensor TFO array, and from 6 to 14 db for the 19-sensor TFO subarray. When averaged over events from several source regions in the distance range 25°<\Delta<000, the signal-to-noise ratio for LASA beams was about 1 db better than that of TFO beams for common events. The improvement in signal-to-noise ratio for LASA beams was found to increase 4 db by changing the number of sensors employed in the beams from 48 to 340 while keeping the minimum sensor spacing \Delta>1 km.

D. Effects of Propagation Paths on Surface-Wave Magnitude Estimates

In this report we investigate the effect of realistic propagation paths on the visual and spectral amplitudes of fundamental mode Rayleigh waves. We snow that the Harkrider amplitude response factor of a layered media should relate directly to a station correction; it varies by a factor of nearly three between oceanic and continental sites. Attenuation due to effective O losses may cause scatter, of over one-half magnitude unit, in teleseismic aplitudes but is unimportant at regional distances. Differences in recorded amplitude caused by dispersion over oceanic and continental paths are sufficient to warrant the application of path corrections to visually measured amplitudes. These differences can be avoided by computing spectra of the signals, or they can be suppressed somewhat by using the results of stationaryphase approximations. More uniform propagation path effects at periods longer than 20 seconds suggest that use of 40 to 50 second waves would provide better seismic discrimination capability and better yield estimation.

E. A Comparative Study of the Elastic Wave Radiation From Earthquakes and Underground Explosions

A detailed analysis of the surface wave radiation from two underground explosions (BILBY and SHOAL) and an earthquake (near Fallon, Nevada) whose epicenter is only 60 km from SHOAL indicates that: (1) at long periods the surface wave radiation from the earthquake can be explained by a pure quadrupole (double-couple) source, but at higher frequencies the radiation pattern shows asymmetries which suggest effects due to rupture propagation which require higher-order multiple terms in the source equivalent representation; (2) the surface waves from the explosions can be explained by superposed monopole and quadrupole sources, with no indication of high-order multipole terms, at least in the frequency range comparable to that in which the earthquake signal was recorded; (3) a principal conclusion of the study is that the anomalous radiation from explosions is probably due to stress

relaxation around the shock-generated shatter zone and not due to earthquake triggering.

A comparative analysis of SHOAL and FALLON shows that:
(1) the ratio of the Love wave amplitude generated by the earthquake to the Love wave amplitude from the explosion is proportional to the period, which implies a larger source dimension for FALLON; (2) the normalized spectral ratio of Love wave amplitude to Rayleigh wave amplitude, considered as a function of period, is near unity for the explosions but larger for the earthquake by a factor of two or three, and increasing with period. These differences might be useful in distinguishing earthquakes from explosions (at least in the magnitude range of the events used in this study, 4.4 and above), as well as for estimating source parameters (such as stress) which are of fundamental geophysical interest.

F. Automatic Network Detection

The theory of automatic detection at a seismic array by means of an F statistic is extended in this study to a network of such arrays. The arrays may have equal or different expected signal-to-noise ratios. Two techniques are discussed: (1) the composite F detector in which a vote is taken among the arrays; (2) a multi-array F detector in which the original data from the independent arrays are combined to form one F statistic. The detectors are found to be nearly equal in detection capability, with the multi-array detector superior by 1-2 dB in the cases examined. For example, with 22 independent arrays of 6 elements each, assuming equal expected signal-to-noise values, the two detectors are 5.4 and 4.3 dB worse, respectively, than an F detector would be operating on a beam of 6x22=132 channels with perfect signal correlation.

G. Source Time Functions and Spectra for Underground Nuclear Explosions

THE SHEET SH

This analysis reveals that Haskell's model for explosion source time functions and spectra fails to satisfy data in the short-period band recorded teleseismically from the three Amchitka Island underground nuclear tests: LONG SHOT, MILROW and CANNIKAN. A more recent model due to Mueller and Murphy satisfies the data quite well. The difference in the two models is basically in the falloff at high frequencies. A simple revision of Haskell's model produces waveforms and spectra nearly identical to ones from Mueller and Murphy's model. This revision requires velocity waveforms to have a rise time of extremely short duration at the elastic boundary, a premise validated by actual near-field measurements.

Waveforms are derived from the revised Haskell model and the Mueller and Murphy model and illustrated for pressure at the elastic boundary, reduced displacement potential at the elastic boundary, and far-field displacement. Corresponding spectra are derived and illustrated.

III. SUPPORT AND SERVICE TASKS

In addition to the research studies discussed above the SDL completed the following support and service tasks:

A. Data Cataloging, Classifying and Retrieval

The library contains digitized seismograms and digital and analog magnetic tapes. Station logs corresponding to each data set are arranged chronologically either in loose-leaf binders or in file cabinets.

At the end of the first quarter of 1972 the library contained approximately:

20,154	digitized seismograms;
4,323	digitized magnetic tapes;
33,099	analog magnetic tapes;

as well as 16 mm film data recorded at seismic observatories during the period September 1960 to the present, and 35 mm film data recorded at LRSM and portable stations during the interval September 1961 to the present.

Although the proportion of digital tapes assigned to a specific function changes constantly, the library consisted of the following groups at the end of the reporting period:

279	UBO multiplexed;
1,615	LASA multiplored;
409	LASA demulti, 1;
432	TFO-37 multipl ed;
98	TFO-37 permanent data;
1,490	Scratch, save and A/D (approximate).

held took before the concession in the contraction of the contraction

The analog magnetic tape library consisted of the following groups at the end of March:

8,765	compressed;
488	composites;
18,007	save (uncompressed)
5,839	uncompressed field tapes (March
•	1970 through March 1972)

B. Equipment Modifications

No equipment modifications were made during the reporting period.

C. Maintain and Operate Equipment

The armature on disk number zero shorted to ground during March and was replaced with a comparable unit from disk number 15. Although disk 15 was rendered inoperable as a result,

the overall capability of the 818 bisk File is only slightly impaired, and the bad armature will not be replaced.

The purchase order is fully approved for the acquisition of the PDP-15/50 system. The Digital Equipment Corporation has confirmed a delivery date of 01 June 1972 for all the system excluding the 1600 b.p.1./9 track tape units which will be delayed about 60 days.

D. Digital Programming

The conversion of Fortran 63 programs to Fortran IV is now proceeding at a faster rate.

E. VELA and PRIME ARGUS Data Copies

During the past year the SDL supplied data or computer services to the following:

Air Force Cambridge Research Laboratory Air Force Office of Scientific Research American Electronic Laboratories Brown University California Institute of Technology Commonwealth of Australia, Dept. of National Development Department of Energy, Mines and Resources, Ottawa, Canada General Atronics Corporation IBM Lawrence Livermore Laboratory MIT, Lincoln Laboratory National Oceanic Atmospheric Administration Pennsylvania State University Stanford University University of Alaska University of Washington University of Wisconsin U. S. Arms Control and Disarmament Agency U. S. Department of Commerce Wright-Patterson Air Force Base

Proposition of the contract of

F. Analog Field Tape Supply

No analog tapes were returned to the field during the reporting period. About 525 TFO analog tapes will be prepared for shipment to Garland early in April.

G. Array Data Service

LASA weekly event summaries through 25 March 1972 were distributed to a revised list of addressees approved by the government.